



减速比 (Ratio i)	i 推荐	60/64/80/100/120/160/200		未注线性尺寸极限偏差 Unmarked tolerance	
	i 不推荐	256/320	512	0.5-3	$\pm 0.2$
额定承载扭矩 (Rated load torque)	Nm	345	265	3-6	$\pm 0.3$
最大加速力矩 (Max. acceleration torque)	Nm	621	477	6-30	$\pm 0.5$
急停扭矩 (Emergency stop torque)	Nm	1035	795	30-120	$\pm 0.8$
*备注三级减速机需与厂家沟通				120-400	$\pm 1.2$
				400-1000	$\pm 2$
精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	6700N	空载力矩 20℃ (No-load torque)	$\leq 0.36Nm$		
容许最大轴向载荷 (Max. axial load)	3300N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	AB115L3-i-P2-S2 24-58-110-145-M8	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	$\geq 20000h$		
噪音 (Noise)	$\leq 63db$	防护等级 (Protection grade)	IP54	A. AB. 115.	
回程间隙 (Backlash)	9arcmin	AB 系列	Tel/电话: 0533-6285333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		
		P2 L3			