




A

B



C

D



減速比 (Ratio i)	i	3	4	5	6	7	8	9	10
額定承載扭矩(Rated load torque)	Nm	220	345	335	300	290	265	255	255
最大加速力矩 (Max.acceleration torque)	Nm	396	621	603	540	522	477	459	459
急停扭矩 (Emergency stop torque)	Nm	660	1035	1005	900	870	795	765	765

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load)	6700N	空载力矩 (No-load torque)			≤ 0.36Nm	
容许最大轴向载荷 (Max. axial load)	3300N	润滑 (Lubrication)			合成润滑油	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h	
噪音 (Noise)	≤ 68db	防护等级 (Protection grade)			IP54	
回程间隙 (Backlash)	9arcmin		ABR 系列	Tel/电话: 0533-6288333 6288444		<b>A. ABR. 115.</b>
			P2 L1	Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		