



| | | | | | |
|-----------------------------------|-------|--------------------------|------|----------------------------------|-----------|
| | | | | 未注线性尺寸极限偏差 Unmarked tolerance | |
| 减速比 (Ratio i) | i 推荐 | 60/64/80/100/120/160/200 | | 0.5-3 | ± 0.2 |
| | i 不推荐 | 256/320 | 512 | 3-6 | ± 0.3 |
| 额定承载扭矩 (Rated load torque) | Nm | 700 | 510 | 6-30 | ± 0.5 |
| 最大加速力矩 (Max. acceleration torque) | Nm | 1260 | 918 | 30-120 | ± 0.8 |
| 急停扭矩 (Emergency stop torque) | Nm | 2100 | 1530 | 120-400 | ± 1.2 |
| *备注三级减速机需与厂家沟通 | | | | 400-1000 | ± 2 |

| 精密行星减速机技术参数 | | | | | 精密行星减速机 Precision Planetary Gear Boxes | |
|------------------------------|-----------|--------------------------------|-------|---|--|--|
| 容许最大径向载荷 (Max. radial load) | 16000N | 空载力矩 (No-load torque) | | ≤ 0.72Nm | | |
| 容许最大轴向载荷 (Max. axial load) | 8000N | 润滑 (Lubrication) | | 合成润滑脂 | | |
| 额定输入转速 (Nominal input speed) | 1000r/min | 使用环境温度 (Operation temperature) | | -15℃~+90℃ | | |
| 最大输入转速 (Max input speed) | 2000r/min | 使用寿命 (Service life) | | ≥20000h | | |
| 噪音 (Noise) | ≤ 74db | 防护等级 (Protection grade) | | IP54 | | |
| 回程间隙 (Backlash) | 16arcmin | | ABR系列 | Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn | | |
| | | | P2 L3 | | | |
| | | | | | A. ABR. 220. | |