



| 未注线性尺寸极限偏差 Unmarked tolerance | |
|----------------------------------|-----------|
| 0.5-3 | ± 0.2 |
| 3-6 | ± 0.3 |
| 6-30 | ± 0.5 |
| 30-120 | ± 0.8 |
| 120-400 | ± 1.2 |
| 400-1000 | ± 2 |

| 精密行星减速机技术参数 | | | | | 精密行星减速机 Precision Planetary Gear Boxes | |
|------------------------------|-----------|--------------------------------|--|---|--|--|
| 容许最大径向载荷 (Max. radial load) | 9600N | 空载力矩 (No-load torque) | | ≤ 0.72Nm | | |
| 容许最大轴向载荷 (Max. axial load) | 4800N | 润滑 (Lubrication) | | 合成润滑油 | | |
| 额定输入转速 (Nominal input speed) | 2000r/min | 使用环境温度 (Operation temperature) | | -15℃~+90℃ | | |
| 最大输入转速 (Max input speed) | 4000r/min | 使用寿命 (Service life) | | ≥20000h | | |
| 噪音 (Noise) | ≤ 70db | 防护等级 (Protection grade) | | IP54 | | |
| 回程间隙 (Backlash) | 11arcmin | ABR 系列 | | Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn | | |
| | | P2 L2 | | | | |
| | | | | | A. ABR. 142. | |