

A

B

C

D

A

B

C

D

1

2

3




4

5

6

输入端 Input

输出端 Output



								未注线性尺寸极限偏差 Unmarked tolerance	
								0.5-3	±0.2
减速比 (Ratio i)	i推荐	12/16/20/28	15/25/35/40		70			3-6	±0.3
	i不推荐		30/45/50	60		64/80	90	6-30	±0.5
额定承载扭矩(Rated load torque)	Nm	1568	1431	1376	1151	1000	910	30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	2822.4	2575.8	2477	2072	1800	1638	120-400	±1.2
急停扭矩 (Emergency stop toque)	Nm	4704	4293	4128	3453	3000	2730	400-1000	±2
精密行星减速机技术参数								精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	14000N	空载力矩20℃ (No-load torque)			≤ 0.36Nm				AB180L2-i-P2-S2 38-80-180-215-M12
容许最大轴向载荷 (Max.axial load)	7000N	润滑(Lubrication)			合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)			-15℃~+90℃				
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)			≥20000h				
噪音 (Noise)	≤ 67db	防护等级 (Protection grade)			IP54			A. AB.	180.
回程间隙 (Backlash)	9arcmin	AB系列 P2 L2			Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				

1

2

3

4

5

6