

1 2 3 4 5 6

A

B

C



D

A

B

C

D



减速比 (Ratio i)	i 推荐	12/16/20/32	15/25/35/40		70		
	i 不推荐		30/45/50	60		64/80	90
额定承载扭矩 (Rated load torque)	Nm	1568	1431	1376	1151	1000	910
最大加速力矩 (Max. acceleration torque)	Nm	2822.4	2575.8	2477	2072	1800	1638
急停扭矩 (Emergency stop torque)	Nm	4704	4293	4128	3453	3000	2730

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	14000N	空载力矩 (No-load torque)		≤ 1.5Nm		
容许最大轴向载荷 (Max. axial load)	7000N	润滑 (Lubrication)		合成润滑油		
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 72db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	13arcmin	ABR 系列		Tel/电话: 0533-6288333 6288444		
		P2 L2		Fax/传真: 0533-6288411		
				Web/网址: www.newstart.cn		
				A. ABR. 180.		

1 2 3 4 5 6