

1

2

3

4

5

6

A

B

C



D

A

B

C

D



减速比 (Ratio i)	i	3	4	5	6	7	8	9	10
额定承载扭矩 (Rated load torque)	Nm	1186	1568	1431	1376	1151	1000	910	910
最大加速力矩 (Max. acceleration torque)	Nm	2134.8	2822	2576	2477	2072	1800	1638	1638
急停扭矩 (Emergency stop torque)	Nm	3558	4704	4293	4128	3453	3000	2730	2730

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	14000N	空载力矩 (No-load torque)		≤ 1.5Nm	
容许最大轴向载荷 (Max. axial load)	7000N	润滑 (Lubrication)		合成润滑脂	
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (operation temperature)		-15℃~+90℃	
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)		≥20000h	
噪音 (Noise)	≤ 72db	防护等级 (Protection grade)		IP54	
回程间隙 (Backlash)	11arcmin	ABR系列		Tel/电话: 0533-6288333 6288444	
		P2 L1		Fax/传真: 0533-6288411	
				Web/网址: www.newstart.cn	
				A. ABR. 180.	

1

2

3

4

5

6