

A

B

C


D


A

B

C

D



减速比 (Ratio i)	i 推荐	60/64/80/100/120/160/200		未注线性尺寸极限偏差 Unmarked tolerance	
	i 不推荐	256/320	512	0.5-3	± 0.2
额定承载扭矩 (Rated load torque)	Nm	1568	1000	3-6	± 0.3
最大加速力矩 (Max. acceleration torque)	Nm	2822.4	1800	6-30	± 0.5
急停扭矩 (Emergency stop torque)	Nm	4704	3000	30-120	± 0.8
*备注三级减速机需与厂家沟通				120-400	± 1.2
				400-1000	± 2
精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	14000N	空载力矩 20℃ (No-load torque)	$\leq 0.72Nm$		
容许最大轴向载荷 (Max. axial load)	7000N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)	$-15^{\circ}C \sim +90^{\circ}C$	AB180L3-i-P2-S2 32-58-130-165-M8	
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)	$\geq 20000h$		
噪音 (Noise)	$\leq 67db$	防护等级 (Protection grade)	IP54	A. AB. 180.	
回程间隙 (Backlash)	9arcmin	AB 系列	Tel/电话: 0533-6285333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		
		P2 L3			