


								未注线性尺寸极限偏差 Unmarked tolerance	
								0.5-3	±0.2
减速比 (Ratio i)	i 推荐	12/16/20/28	15/25/35/40		70			3-6	±0.3
	i 不推荐		30/45/50	60		64/80	90	6-30	±0.5
额定承载扭矩(Rated load torque)	Nm	60	60	52	50	45	42	30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	108	108	93.6	90	81	75.6	120-400	±1.2
急停扭矩 (Emergency stop toque)	Nm	180	180	156	150	135	126	400-1000	±2
精密行星减速机技术参数								精密行星减速机	
容许最大径向载荷 (Max.radial load)		1500N	空载力矩20℃ (No-load torque)		≤ 0.1Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		760N	润滑(Lubrication)		合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃			AB090L2-i-P2-S2	
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)		≥20000h				
噪音 (Noise)		≤ 60db	防护等级 (Protection grade)		IP54			8-24-38.1-□47.14-M4	
回程间隙 (Backlash)		7arcmin	AB系列		Tel/电话: 0533-6288333 6288444			A. AB. 060.	
			P2 L2		Fax/传真: 0533-6288411				
					Web/网址: www.newstart.cn				