


减速比 (Ratio i)	i	3	4	5	6	7	8	9	10	5-6	±0.3
额定承载扭矩(Rated load torque)	Nm	55	65	60	52	50	45	42	42	6-30	±0.5
最大加速力矩 (Max.acceleration torque)	Nm	99	117	108	93.6	90	81	75.6	75.6	30-120	±0.8
急停扭矩 (Emergency stop torque)	Nm	165	195	180	156	150	135	126	126	120-400	±1.2
精密行星减速机技术参数										精密行星减速机	
容许最大径向载荷 (Max.radial load)	1500N	空载力矩20℃ (No-load torque)				≤ 0.1Nm				Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)	760N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)				 纽氏达特	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)				-15℃ +90℃					
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h				AB060L1-i-P2-S2	
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)				IP54				14-30-50-70-M5	
回程间隙 (Backlash)	5arcmin	AB系列				Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				A. AB. 060.	
		P2 L1									