


				Unmarked tolerance		
减速比 (Ratio i)	i推荐	60/64/80/100/120/160/200			0.5-3	±0.2
	i不推荐	256/320		512	3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	65		45	6-30	±0.5
最大加速力矩 (Max.acceleration torque)	Nm	117		81	30-120	±0.8
急停扭矩 (Emergency stop toque)	Nm	195		135	120-400	±1.2
*备注三级减速机需与厂家沟通					400-1000	±2
精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max.radial load)	1500N	空载力矩 (No-load torque)		≤ 0.1Nm		
容许最大轴向载荷 (Max.axial load)	760N	润滑 (Lubrication)		合成润滑油		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		ABR060L3-i-P2-S2 8-24-30-45-M3
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	13arcmin			ABR系列	A. ABR. 060.	
				P2 L3		
				Tel/电话: 0533-6288333 6288444		
				Fax/传真: 0533-6288411		
				Web/网址: www.newstart.cn		

