


减速比 (Ratio i)	i	3	4	5	6	7	8	9	10
额定承载扭矩 (Rated load torque)	Nm	55	65	60	52	50	45	42	42
最大加速力矩 (Max. acceleration torque)	Nm	99	117	108	93.6	90	81	75.6	75.6
急停扭矩 (Emergency stop torque)	Nm	165	195	180	156	150	135	126	126

精密行星减速机技术参数				
容许最大径向载荷 (Max. radial load)	1500N	空载力矩 (No-load torque)	$\leq 0.1Nm$	
容许最大轴向载荷 (Max. axial load)	760N	润滑 (Lubrication)	合成润滑脂	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	$-15^{\circ}C \sim +90^{\circ}C$	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	$\geq 20000h$	
噪音 (Noise)	$\leq 63db$	防护等级 (Protection grade)	IP54	
回程间隙 (Backlash)	9arcmin	ABR系列	Tel/电话: 0533-6288333 6288444	
		P2 L1	Fax/传真: 0533-6288411	
			Web/网址: www.newstart.cn	

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2
精密行星减速机 Precision Planetary Gear Boxes	
	
ABR060L1-i-P2-S2	
8-24-38.1-1147.14-M4	
A. ABR.	060.