




1 2 3 4 5 6

A

B

C

D




A

B

C

D

| | | | | | | | | | | | |
|----------------------------------|-----------|-------------------------------|-----|-----|-------|--------------------------|------------------------------|-----|-----|---|------|
| 减速比 (Ratio i) | i | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 6-30 | ±0.5 |
| 额定承载扭矩(Rated load torque) | Nm | 135 | 165 | 160 | 145 | 135 | 115 | 105 | 105 | 30-120 | ±0.8 |
| 最大加速力矩 (Max.acceleration torque) | Nm | 243 | 297 | 288 | 261 | 243 | 207 | 189 | 189 | 120-400 | ±1.2 |
| 急停扭矩 (Emergency stop torque) | Nm | 405 | 495 | 480 | 435 | 405 | 345 | 315 | 315 | 400-1000 | ±2 |
| 精密行星减速机技术参数 | | | | | | | | | | 精密行星减速机 | |
| 容许最大径向载荷 (Max.radial load) | 3200N | 空载力矩20℃(No-load torque) | | | | ≤ 0.2Nm | | | | <div></div> <div>AB090L1-i-P2-S2 19-40-70-90-M5</div> <div>A. AB. 090.</div> | |
| 容许最大轴向载荷 (Max.axial load) | 1600N | 润滑(Lubrication) | | | | 合成润滑油 (Synthetic grease) | | | | | |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度(Operation temperature) | | | | -15℃~+90℃ | | | | | |
| 最大输入转速 (Max input speed) | 6000r/min | 使用寿命(Service life) | | | | ≥20000h | | | | | |
| 噪音 (Noise) | ≤ 60db | 防护等级(Protection grade) | | | | IP54 | | | | | |
| 回程间隙 (Backlash) | 5arcmin | | | | AB系列 | | Tel/电话: 0533-6288333 6288444 | | | | |
| | | | | | P2 L1 | | Fax/传真: 0533-6288411 | | | | |
| | | | | | | | Web/网址: www.newstart.cn | | | | |

1 2 3 4 5 6