


减速比 (Ratio i)	i 推荐	60/64/80/100/120/160/200		未注线性尺寸极限偏差 Unmarked tolerance	
	i 不推荐	256/320	512	0.5-3	±0.2
额定承载扭矩 (Rated load torque)	Nm	165	115	3-6	±0.3
最大加速力矩 (Max. acceleration torque)	Nm	297	207	6-30	±0.5
急停扭矩 (Emergency stop torque)	Nm	495	345	30-120	±0.8
*备注三级减速机需与厂家沟通				120-400	±1.2
精密行星减速机技术参数				400-1000	±2
容许最大径向载荷 (Max. radial load)	3200N	空载力矩 20℃ (No-load torque)	≤ 0.2Nm	精密行星减速机 Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)	1600N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h	AB090L3-i-P2-S2	
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)	IP54	19-40-70-90-M6	
回程间隙 (Backlash)	9arcmin	AB 系列	Tel/电话: 0533-6285333 6288444	A. AB. 090.	
		P2 L3	Fax/传真: 0533-6288411		
			Web/网址: www.newstart.cn		