


				未注线性尺寸极限偏差 Unmarked tolerance	
减速比 (Ratio i)	i 推荐	60/64/80/100/120/160/200		0.5-3	±0.2
	i 不推荐	256/320	512	3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	165	115	6-30	±0.5
最大加速力矩 (Max. acceleration torque)	Nm	297	207	30-120	±0.8
急停扭矩 (Emergency stop torque)	Nm	495	345	120-400	±1.2
*备注三级减速机需与厂家沟通				400-1000	±2

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes		
容许最大径向载荷 (Max. radial load)	3200N	空载力矩 (No-load torque)		≤ 0.2Nm		ABR090L3-i-P2-S2 19-40-80-100-M6	
容许最大轴向载荷 (Max. axial load)	1600N	润滑 (Lubrication)		合成润滑油			
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃			
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h			
噪音 (Noise)	≤ 65db	防护等级 (Protection grade)		IP54	A. ABR. 090.		
回程间隙 (Backlash)	13arcmin	ABR 系列		Tel/电话: 0533-6288333 6288444			
		P2 L3		Fax/传真: 0533-6288411 Web/网址: www.newstart.cn			