


								未注线性尺寸极限偏差 Unmarked tolerance	
								0.5-3	±0.2
减速比 (Ratio i)	i推荐	12/16/20/28	15/25/35/40		70			3-6	±0.3
	i不推荐		30/45/50	60		64/80	90	6-30	±0.5
额定承载扭矩(Rated load torque)	Nm	165	160	145	135	115	105	30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	297	288	261	243	207	189	120-400	±1.2
急停扭矩 (Emergency stop toque)	Nm	495	480	435	405	345	315	400-1000	±2
精密行星减速机技术参数								精密行星减速机	
容许最大径向载荷 (Max.radial load)	3200N	空载力矩20℃ (No-load torque)			≤ 0.2Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)	1600N	润滑(Lubrication)			合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)			-15℃~+90℃			AB090L2-i-P2-S2	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h			22-58-110-145-M8	
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)			IP54				
回程间隙 (Backlash)	7arcmin			AB系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn			A. AB. 090.	
				P2 L2					