


减速比 (Ratio i)	i推荐	60/64/80/100/120/160/200			未注线性尺寸极限偏差 Unmarked tolerance
	i不推荐	256/320		512	
额定承载扭矩 (Rated load torque)	Nm	165		115	0.5-3 ±0.2
最大加速力矩 (Max.acceleration torque)	Nm	297		207	3-6 ±0.3
急停扭矩 (Emergency stop torque)	Nm	495		345	6-30 ±0.5
*备注三级减速机需与厂家沟通					30-120 ±0.8
					120-400 ±1.2
					400-1000 ±2
精密行星减速机技术参数					精密行星减速机
容许最大径向载荷 (Max.radial load)	3200N	空载力矩20℃ (No-load torque)	≤ 0.2Nm		Precision Planetary Gear Boxes
容许最大轴向载荷 (Max.axial load)	1600N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)		 紐氏達特 <small>NEWSTART</small>
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)	IP54		
回程间隙 (Backlash)	9arcmin		AB系列	Tel/电话: 0533-6288333 6289444	A. AB. 090.
			P2 L3	Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	