


减速比 (Ratio i)	i	3	4	5	6	7	8	9	10	30	±0.5
额定承载扭矩 (Rated load torque)	Nm	135	165	160	145	135	115	105	105	30-120	±0.5
最大加速力矩 (Max. acceleration torque)	Nm	243	297	288	261	243	207	189	189	120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	405	495	480	435	405	345	315	315	400-1000	±2
精密行星减速机技术参数										精密行星减速机	
容许最大径向载荷 (Max. radial load)	3200N	空载力矩20°C (No-load torque)				≤ 0.2Nm				Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)	1600N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)				 纽氏达特	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)				-15°C~+90°C				AB090L1-i-P2-S2	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h				19-40-80-100-M6	
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)				IP54					
回程间隙 (Backlash)	5arcmin			AB系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网站: www.newstar.cn				A. AB. 090.	
				P2 L1							