



减速比 (Ratio i)	60	64	80	100	120	160	200	256	320	512
额定承载扭矩 (Rated load torque) Nm	700	700	700	700	700	700	650	700	650	510
最大加速力矩 (Max. acceleration torque) Nm	1260	1260	1260	117	1260	1260	1170	1260	1170	918
急停扭矩 (Emergency stop torque) Nm	2100	2100	2100	195	2100	2100	1950	2100	1950	1530

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数

容许最大径向载荷 (Max. radial load)	13700N	空载力矩20℃ (No-load torque)	≤ 0.72Nm
容许最大轴向载荷 (Max. axial load)	8800N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise) ≤	65db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	9arcmin	AD系列	Tel/电话: 0533-6288333 6288444
		P2 L3	Fax/传真: 0533-6288411
			Web/网址: www.newstart.cn

精密行星减速机

Precision Planetary Gear Boxes

AD140L3-i-P2-0P2
32-58-130-165-M10

A. AD. 140.