



減速比 (Ratio i)		12	15	16	25	32	35	40	30	50	64
額定承載扭矩 (Rated load torque)	Nm	1483	1200	1483	1200	1483	1200	1200	1200	1200	1000
最大加速力矩 (Max. acceleration torque)	Nm	2669	2160	2669	2160	2669	2160	2160	2160	2160	1800
急停扭矩 (Emergency stop torque)	Nm	4449	3600	4449	3600	4449	3600	3600	3600	3600	3000

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	26600N	空载力矩20℃ (No-load torque)		≤ 1.5Nm		
容许最大轴向载荷 (Max.axial load)	18000N	润滑 (Lubrication)		合成润滑油 (Synthetic grease)		
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	4000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 67db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	9arcmin		AD系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		
			P2 L2			
				A. AD. 200.		