



| | | | | | | | | | | |
|--------------------------------------|------|------|------|------|------|------|------|--------|------|------|
| 减速比 (Ratio i) | 60 | 64 | 80 | 100 | 120 | 160 | 200 | 256 | 320 | 512 |
| 额定承载扭矩 (Rated load torque) Nm | 1483 | 1483 | 1483 | 1483 | 1483 | 1483 | 1200 | 1483 | 1200 | 1000 |
| 最大加速力矩 (Max. acceleration torque) Nm | 2669 | 2669 | 2669 | 2669 | 2669 | 2669 | 2160 | 2669.4 | 2160 | 1800 |
| 急停扭矩 (Emergency stop torque) Nm | 4449 | 4449 | 4449 | 4449 | 4449 | 4449 | 3600 | 4449 | 3600 | 3000 |

| 未注线性尺寸极限偏差 Unmarked tolerance | |
|----------------------------------|------|
| 0.5-3 | ±0.2 |
| 3-6 | ±0.3 |
| 6-30 | ±0.5 |
| 30-120 | ±0.8 |
| 120-400 | ±1.2 |
| 400-1000 | ±2 |

精密行星减速机技术参数

| | | | |
|------------------------------|-----------|--------------------------------|------------------------------|
| 容许最大径向载荷 (Max. radial load) | 26600N | 空载力矩20℃ (No-load torque) | ≤ 1.5Nm |
| 容许最大轴向载荷 (Max. axial load) | 18000N | 润滑 (Lubrication) | 合成润滑脂 (Synthetic grease) |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度 (Operation temperature) | -15℃~+90℃ |
| 最大输入转速 (Max input speed) | 6000r/min | 使用寿命 (Service life) | ≥20000h |
| 噪音 (Noise) | ≤ 67db | 防护等级 (Protection grade) | IP54 |
| 回程间隙 (Backlash) | 11arcmin | AD系列 | Tel/电话: 0533-6288333 6288444 |
| | | P2 L3 | Fax/传真: 0533-6288411 |
| | | | Web/网址: www.newstart.cn |

精密行星减速机

Precision Planetary Gear Boxes



AD200L3-i-P2-OP2
32-58-130-165-M10

A. AD. 200.