

1

2

3

4

5


6

A


B

C

D



输出端



减速比 (Ratio i)	12	16	15	25	32	40	30	50	64
额定承载扭矩 (Rated load torque) Nm	1483	1483	1200	1200	1483	1200	1200	1200	1000
最大加速力矩 (Max. acceleration torque) Nm	2669	2669	2160	2160	2669	2160	2160	2160	1800
急停扭矩 (Emergency stop torque) Nm	4449	4449	3600	3600	4449	3600	3600	3600	3000

精密行星减速机技术参数

容许最大径向载荷 (Max. radial load)	26600N	空载力矩20℃ (No-load torque)	≤ 1.5Nm
容许最大轴向载荷 (Max. axial load)	18000N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise)	≤ 70db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	15arcmin	ADR系列	Tel/电话: 0533-6288333 6288444
		P2 L2	Fax/传真: 0533-6288411
			Web/网址: www.newstart.cn

未注线性尺寸极限偏差
Unmarked tolerance

0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机
Precision Planetary
Gear Boxes



ADR200L2-i-P2-OP2
32-58-130-165-M10

A. ADR. 200.

1

2

3

4

5

6

A

B

C

D