


减速比 (Ratio i)		12	15	16	25	32	35	40	30	50	64
额定承载扭矩 (Rated load torque)	Nm	23	21	23	21	23	21	21	21	21	18
最大加速力矩 (Max.acceleration torque)	Nm	41.4	37.8	41.4	37.8	41.4	37.8	37.8	37.8	37.8	32.4
急停扭矩 (Emergency stop toque)	Nm	69	63	69	63	69	63	63	63	63	54

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	800N	空载力矩20℃ (No-load torque)	≤ 0.05Nm	 ADR047L2-i-P2-OP2 8-25-30-45-M3	
容许最大轴向载荷 (Max.axial load)	500N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	A. ADR 047.	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)	≤ 56db	防护等级 (Protection grade)	IP54	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	
回程间隙 (Backlash)	11arcmin	ADR系列	P2 L2		