


減速比 (Ratio i)		12	15	16	25	32	35	40	30	50	64
額定承载扭矩 (Rated load torque)	Nm	65	60	64	60	65	60	60	60	60	45
最大加速力矩 (Max. acceleration torque)	Nm	117	108	115.2	108	117	108	108	108	108	81
急停扭矩 (Emergency stop torque)	Nm	195	180	192	180	195	180	180	180	180	135

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load)		3150N	空载力矩20℃ (No-load torque)		≤ 0.1Nm	Precision Planetary Gear Boxes
容许最大轴向载荷 (Max. axial load)		2400N	润滑 (Lubrication)		合成润滑油 (Synthetic grease)	
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃	AD064L2-i-P2-0P2 14-30-50-70-M5
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)		≥20000h	
噪音 (Noise)		≤ 60db	防护等级 (Protection grade)		IP54	A. AD. 064.
回程间隙 (Backlash)		7arcmin	AD系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	
			P2 L2			