

1

2

3

4

5




6

A

B

C

D



减速比 (Ratio i)	60	64	80	100	120	160	200	256	320	512
额定承载扭矩 (Rated load torque) Nm	165	165	165	165	165	165	160	165	160	115
最大加速力矩 (Max. acceleration torque) Nm	297	297	297	117	297	297	288	297	288	207
急停扭矩 (Emergency stop torque) Nm	495	495	495	195	495	495	480	495	480	345

精密行星减速机技术参数

容许最大径向载荷 (Max. radial load)	4500N	空载力矩20℃ (No-load torque)	$\leq 0.2Nm$
容许最大轴向载荷 (Max. axial load)	3500N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	$\geq 20000h$
噪音 (Noise)	$\leq 65db$	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	13arcmin	ADR系列	
		P2 L3	
		Tel/电话: 0533-6288333 6288444	
		Fax/传真: 0533-6288411	
		Web/网址: www.newstart.cn	

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机
Precision Planetary
Gear Boxes



ADR090L3-i-P2-0P2
19-40-70-90-M5

A. ADR. 090.

1

2

3

4

5

6

A

B

C

D