


| | | | | | | | | | | | |
|-----------------------------------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 減速比 (Ratio i) | | 60 | 64 | 80 | 100 | 120 | 160 | 200 | 256 | 320 | 512 |
| 額定承载扭矩 (Rated load torque) | Nm | 165 | 165 | 165 | 165 | 165 | 165 | 160 | 165 | 160 | 115 |
| 最大加速力矩 (Max. acceleration torque) | Nm | 297 | 297 | 297 | 117 | 297 | 297 | 288 | 297 | 288 | 207 |
| 急停扭矩 (Emergency stop torque) | Nm | 495 | 495 | 495 | 195 | 495 | 495 | 480 | 495 | 480 | 345 |

| 未注线性尺寸极限偏差 Unmarked tolerance | |
|----------------------------------|-----------|
| 0.5-3 | ± 0.2 |
| 3-6 | ± 0.3 |
| 6-30 | ± 0.5 |
| 30-120 | ± 0.8 |
| 120-400 | ± 1.2 |
| 400-1000 | ± 2 |

| 精密行星减速机技术参数 | | | | | 精密行星减速机 Precision Planetary Gear Boxes | |
|------------------------------|-----------|--------------------------------|-------|------------------------------|--|--|
| 容许最大径向载荷 (Max. radial load) | 4500N | 空载力矩20℃ (No-load torque) | | ≤ 0.2Nm | | |
| 容许最大轴向载荷 (Max. axial load) | 3500N | 润滑 (Lubrication) | | 合成润滑脂 (Synthetic grease) | | |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度 (Operation temperature) | | -15℃~+90℃ | | |
| 最大输入转速 (Max input speed) | 6000r/min | 使用寿命 (Service life) | | ≥20000h | | |
| 噪音 (Noise) | ≤ 60db | 防护等级 (Protection grade) | | IP54 | | |
| 回程间隙 (Backlash) | 9arcmin | | AD系列 | Tel/电话: 0533-6288333 6288444 | | |
| | | | P2 L3 | Fax/传真: 0533-6288411 | | |
| | | | | Web/网址: www.newstart.cn | | |



AD090L3-i-P2-0P2
14-30-50-70-M4

A. AD. 090.