


减速比 (Ratio i)	12	16	15	25	32	40	30	50	64
额定承载扭矩 (Rated load torque) Nm	165	165	160	160	165	160	160	160	115
最大加速力矩 (Max.acceleration torque) Nm	297	297	288	288	297	288	288	288	207
急停扭矩 (Emergency stop torque) Nm	495	495	480	480	495	480	480	480	345

精密行星减速机技术参数			
容许最大径向载荷 (Max.radial load)	4500N	空载力矩20℃ (No-load torque)	≤ 0.2Nm
容许最大轴向载荷 (Max.axial load)	3500N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise)	≤ 65db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	11arcmin	ADR系列	
		P2 L2	
		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2
精密行星减速机 Precision Planetary Gear Boxes	
	
ADR090L2-i-P2-OP2 22-58-110-145-M8	
A. ADR.	090.