


|                                  |    |     |     |     |     |     |     |     |     |     |     |
|----------------------------------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 減速比 (Ratio i)                    |    | 12  | 15  | 16  | 25  | 32  | 35  | 40  | 30  | 50  | 64  |
| 額定承載扭矩 (Rated load torque)       | Nm | 165 | 160 | 165 | 160 | 165 | 160 | 160 | 160 | 160 | 115 |
| 最大加速力矩 (Max.acceleration torque) | Nm | 297 | 288 | 297 | 288 | 297 | 288 | 288 | 288 | 288 | 207 |
| 急停扭矩 (Emergency stop touqe)      | Nm | 495 | 480 | 495 | 480 | 495 | 480 | 480 | 480 | 480 | 345 |

| 未注线性尺寸极限偏差<br>Unmarked tolerance |           |
|----------------------------------|-----------|
| 0.5-3                            | $\pm 0.2$ |
| 3-6                              | $\pm 0.3$ |
| 6-30                             | $\pm 0.5$ |
| 30-120                           | $\pm 0.8$ |
| 120-400                          | $\pm 1.2$ |
| 400-1000                         | $\pm 2$   |

| 精密行星减速机技术参数                  |           |                               |       |   | 精密行星减速机<br>Precision Planetary<br>Gear Boxes  |
|------------------------------|-----------|-------------------------------|-------|---|---|
| 容许最大径向载荷 (Max.radial load)   | 4500N     | 空载力矩20℃(No-load torque)       |       | ≤ 0.2Nm   |  |
| 容许最大轴向载荷 (Max.axial load)    | 3500N     | 润滑(Lubrication)               |       | 合成润滑油 (Synthetic grease)  |   |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度(Operation temperature) |       | -15℃~+90℃   |   |
| 最大输入转速 (Max input speed)     | 6000r/min | 使用寿命(Service life)            |       | ≥20000h   |   |
| 噪音 (Noise)                   | ≤ 60db    | 防护等级(Protection grade)        |       | IP54  |   |
| 回程间隙 (Backlash)              | 7arcmin   |                               | AD系列  | Tel/电话: 0533-6288333 6288444<br>Fax/传真: 0533-6288411<br>Web/网址: www.newstart.cn | A. AD. 090.   |
|                              |           |                               | P2 L2 |   |   |