



减速比 (Ratio i)	i	3	4	5	6	7	8	9	10
额定承载扭矩 (Rated load torque)	Nm	220	345	335	300	290	265	255	255
最大加速力矩 (Max. acceleration torque)	Nm	396	621	603	540	522	477	459	459
急停扭矩 (Emergency stop torque)	Nm	660	1035	1005	900	870	795	765	765

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	2900N	空载力矩 (No-load torque)		≤ 0.36Nm		
容许最大轴向载荷 (Max. axial load)	1950N	润滑 (Lubrication)		合成润滑脂		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	5arcmin	AE系列		Tel/电话: 0533-6288333 6288444		
		P2 L1		Fax/传真: 0533-6288411		
				Web/网址: www.newstart.cn		
				A. AE. 120.		