



减速比 (Ratio i)	i推荐	12/16/20/32	15/25/35/40		70			3-6	±0.3
	i不推荐		30/45/50	60		64/80	90	6-30	±0.5
额定承载扭矩(Rated load torque)	Nm	345	335	300	290	265	255	30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	621	603	540	522	477	459	120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	1035	1005	900	870	795	765	400-1000	±2

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	2900N	空载力矩20℃ (No-load torque)		≤ 0.36Nm		
容许最大轴向载荷 (Max. axial load)	1950N	润滑 (Lubrication)		合成润滑油		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃ ~ +90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥ 20000h		
噪音 (Noise)	≤ 68db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	11arcmin	AER系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		
		P2 L2				
					A. AER. 120.	