



减速比 (Ratio i)				未注线性尺寸极限偏差 Unmarked tolerance	
				0.5-3	±0.2
i 推荐 60/64/80/100/120/160/200				3-6	±0.3
i 不推荐 256/320				6-30	±0.5
额定承载扭矩 (Rated load torque) Nm				700	510
最大加速力矩 (Max. acceleration torque) Nm				1260	918
急停扭矩 (Emergency stop torque) Nm				2100	1530
*备注三级减速机需与厂家沟通				30-120	±0.8
精密行星减速机技术参数				120-400	±1.2
容许最大径向载荷 (Max. radial load) 5700N				400-1000	±2
容许最大轴向载荷 (Max. axial load) 3150N				精密行星减速机 Precision Planetary Gear Boxes	
额定输入转速 (Nominal input speed) 2000r/min				空载力矩 (No-load torque) ≤ 0.72Nm	
最大输入转速 (Max input speed) 4000r/min				润滑 (Lubrication) 合成润滑油	
噪音 (Noise) ≤ 65db				使用环境温度 (Operation temperature) -15℃~+90℃	
回程间隙 (Backlash) 11arcmin				使用寿命 (Service life) ≥20000h	
				防护等级 (Protection grade) IP54	
				AE系列	
				Tel/电话: 0533-6288333 6288444	
				Fax/传真: 0533-6288411	
				Web/网址: www.newstart.cn	
				A. AE. 155.	