



减速比 (Ratio i)	i	3	4	5	6	7	8	9	10	6-30	±0.5
额定承载扭矩 (Rated load torque)	Nm	450	700	650	610	540	510	455	455	30-120	±0.8
最大加速力矩 (Max. acceleration torque)	Nm	810	1260	1170	1098	972	918	819	819	120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	1350	2100	1950	1830	1620	1530	1365	1365	400-1000	±2
精密行星减速机技术参数										精密行星减速机	
容许最大径向载荷 (Max. radial load)	5700N	空载力矩 (No-load torque)					≤ 0.72Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)	3150N	润滑 (Lubrication)					合成润滑油			 <b>NEWSTART</b> 纽氏达特	
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度 (Operation temperature)					-15℃~+90℃			AE155L1-i1-P2-S2 32-58-130-165-M10	
最大输入转速 (Max input speed)	4000r/min	使用寿命 (Service life)					≥20000h				
噪音 (Noise)	≤ 65db	防护等级 (Protection grade)					IP54			A. AE. 155.	
回程间隙 (Backlash)	5arcmin				AE系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				
P2 L1											