



减速比 (Ratio i)				未注线性尺寸极限偏差 Unmarked tolerance	
				0.5-3	±0.2
i 推荐 60/64/80/100/120/160/200				3-6	±0.3
i 不推荐 256/320				6-30	±0.5
额定承载扭矩 (Rated load torque) Nm				45	±0.8
最大加速力矩 (Max. acceleration torque) Nm				81	±1.2
急停扭矩 (Emergency stop torque) Nm				135	±2
*备注三级减速机需与厂家沟通				400-1000	±2
精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	950N	空载力矩 (No-load torque)	≤ 0.1Nm	NEWSTART 纽氏达特	
容许最大轴向载荷 (Max. axial load)	740N	润滑 (Lubrication)	合成润滑油		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	AE070L3-i-P2-S2 14-30-50-70-M5	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)	IP54	A. AE. 070.	
回程间隙 (Backlash)	9arcmin	AE系列			
				Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	