



减速比 (Ratio i)	i 推荐	60/64/80/100/120/160/200		未注线性尺寸极限偏差	
	i 不推荐	256/320	512	0.5-3	±0.2
额定承载扭矩 (Rated load torque)	Nm	65	45	3-6	±0.3
最大加速力矩 (Max.acceleration torque)	Nm	117	81	6-30	±0.5
急停扭矩 (Emergency stop torque)	Nm	195	135	30-120	±0.8
				120-400	±1.2
*备注三级减速机需与厂家沟通				400-1000	±2
精密行星减速机技术参数				精密行星减速机	
容许最大径向载荷 (Max.radial load)	950N	空载力矩20℃ (No-load torque)	≤ 0.1Nm	Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)	740N	润滑 (Lubrication)	合成润滑油		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h	AER070L3-i-P2-S2	
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)	IP54	8-24-38.1-□47.14-M4	
回程间隙 (Backlash)	13arcmin	AER系列		A. AER. 070.	
				Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	