



未注线性尺寸极限偏差 Unmarked tolerance							
0.5-3							
±0.2							
3-6							
±0.3							
6-30							
±0.5							
30-120							
±0.8							
120-400							
±1.2							
400-1000							
±2							

精密行星减速机技术参数							
减速比 (Ratio i)	i 推荐	12/16/20/32	15/25/35/40	60	70	80	100
	i 不推荐		30/45/50	60	70	80	100
额定承载扭矩 (Rated load torque)	Nm	65	60	52	50	45	40
最大加速力矩 (Max. acceleration torque)	Nm	117	108	93.6	90	81	72
急停扭矩 (Emergency stop torque)	Nm	195	180	156	150	135	120
容许最大径向载荷 (Max. radial load)	950N	空载力矩 (No-load torque)		≤ 0.1Nm		精密行星减速机	
容许最大轴向载荷 (Max. axial load)	740N	润滑 (Lubrication)		合成润滑油		Precision Planetary Gear Boxes	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		NEWSTART 纽氏达特	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h		AE070L2-i-P2-S2	
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)		IP54		14-30-50-70-M5	
回程间隙 (Backlash)	7arcmin	AE系列		Tel/电话: 0533-6288333 6288444		A. AE. 070.	
		P2 L2		Fax/传真: 0533-6288411			
				Web/网址: www.newstart.cn			