


減速比 (Ratio i)	i	3	4	5	6	7	8	9	10	6-30	±0.5
額定承載扭矩 (Rated load torque)	Nm	135	165	160	145	135	115	105	105	30-120	±0.8
最大加速力矩 (Max. acceleration torque)	Nm	243	297	288	261	243	207	189	189	120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	405	495	480	435	405	345	315	315	400-1000	±2

精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	1600N	空载力矩20℃(No-load torque)	≤ 0.2Nm		
容许最大轴向载荷 (Max.axial load)	1500N	润滑(Lubrication)	合成润滑脂		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)	-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)	≥20000h		AER090L1-i-P2-S2 19-40-70-90-M5
噪音 (Noise)	≤ 65db	防护等级(Protection grade)	IP54		
回程间隙 (Backlash)	9arcmin	AER系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		A. AER. 090.
		P2 L1			