



减速比 (Ratio i)				未注线性尺寸极限偏差 Unmarked tolerance	
				0.5-3	±0.2
i 推荐				60/64/80/100/120/160/200	
i 不推荐				256/320	512
额定承载扭矩 (Rated load torque)		Nm	165	115	3-6
最大加速力矩 (Max. acceleration torque)		Nm	297	207	6-30
急停扭矩 (Emergency stop torque)		Nm	495	345	30-120
*备注三级减速机需与厂家沟通				120-400	±0.8
精密行星减速机技术参数				400-1000	±1.2
容许最大径向载荷 (Max. radial load)		1600N	空载力矩 (No-load torque)	≤ 0.2Nm	±2
容许最大轴向载荷 (Max. axial load)		1500N	润滑 (Lubrication)	合成润滑脂	
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)	≥20000h	
噪音 (Noise)		≤ 60db	防护等级 (Protection grade)	IP54	
回程间隙 (Backlash)		9arcmin	AE系列		
				Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	

精密行星减速机  
Precision Planetary  
Gear Boxes

紐氏達特

AE090L3-i-P2-S2  
14-30-50-70-M4

A. AE. 090.