



				未注线性尺寸极限偏差 Unmarked tolerance	
减速比 (Ratio i)	i 推荐	60/64/80/100/120/160/200		0.5-3	±0.2
	i 不推荐	256/320	512	3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	165	115	6-30	±0.5
最大加速力矩 (Max. acceleration torque)	Nm	297	207	30-120	±0.8
急停扭矩 (Emergency stop torque)	Nm	495	345	120-400	±1.2
*备注三级减速机需与厂家沟通				400-1000	±2
精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	1600N	空载力矩 (No-load torque)	≤ 0.2Nm		
容许最大轴向载荷 (Max. axial load)	1500N	润滑 (Lubrication)	合成润滑油		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	AE090L3-i-P2-S2 19-40-80-100-M6	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)	IP54	A. AE. 090.	
回程间隙 (Backlash)	9arcmin	AE系列			
				Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	