


减速比 (Ratio i)	i 推荐	12/16/20/32	15/25/35/40	70				6-30	±0.5
	i 不推荐		30/45/50	60		64/80	90	30-120	±0.8
额定承载扭矩 (Rated load torque)	Nm	165	160	145	135	115	105	120-400	±1.2
最大加速力矩 (Max. acceleration torque)	Nm	297	288	261	243	207	189	400-1000	±2
急停扭矩 (Emergency stop torque)	Nm	495	480	435	405	345	315		

精密行星减速机技术参数								精密行星减速机	
容许最大径向载荷 (Max. radial load)	1600N	空载力矩 (No-load torque)	≤ 0.2Nm					Precision Planetary	
容许最大轴向载荷 (Max. axial load)	1500N	润滑 (Lubrication)	合成润滑油					Gear Boxes	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃						
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h						
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)	IP54					AE090L2-i-P2-S2	
回程间隙 (Backlash)	7arcmin		AE系列		Tel/电话: 0533-6288333 6288444			A. AE.	090.
			P2 L2		Fax/传真: 0533-6288411				
					Web/网址: www.newstart.cn				