

1

2

3

4

5

6

A

B

C


D

A

B

C

D

减速比 (Ratio i)		3	4	5	6	8	10	3-6	±0.3
额定承载扭矩(Rated load torque) Nm		125	260	230	128	120	70	6-30	±0.5
最大加速力矩 (Max.acceleration torque) Nm		225	468	414	230.4	216	126	30-120	±0.8
急停扭矩 (Emergency stop toque) Nm		375	780	690	384	360	210	120-400	±1.2
								400-1000	±2
精密行星减速机技术参数								精密行星减速机	
容许最大径向载荷 (Max.radial load)		900N	空载力矩20℃ (No-load torque)			≤ 0.36Nm		Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		1200N	润滑 (Lubrication)			合成润滑油 (Synthetic grease)		 紐氏達特	
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃		WPF0115L1-i-P2-S2 35-79-114.3-200-M12	
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)			≥20000h			
噪音 (Noise)		≤ 68db	防护等级 (Protection grade)			IP54		A. WPF. 115.	
回程间隙 (Backlash)		14arcmin				PL系列			
			P2 L1			Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn			

1

2

3

4

5

6