


減速比 (Ratio i)		3	4	5	6	8	10
額定承載扭矩(Rated load torque)	Nm	125	260	230	128	120	70
最大加速力矩 (Max.acceleration torque)	Nm	225	468	414	230.4	216	126
急停扭矩 (Emergency stop toque)	Nm	375	780	690	384	360	210

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机技术参数			
容许最大径向载荷 (Max.radial load)	900N	空载力矩20℃(No-load torque)	≤ 0.36Nm
容许最大轴向载荷 (Max.axial load)	1200N	润滑(Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)	≥20000h
噪音 (Noise)	≤ 68db	防护等级(Protection grade)	IP54
回程间隙 (Backlash)	14arcmin	PL系列	Tel/电话: 0533-6288333 6288444
		P2 L1	Fax/传真: 0533-6288411
			Web/网址: www.newstart.cn

	精密行星减速机 Precision Planetary Gear Boxes
	 紐氏達特
	WPF0115L1-i-P2-S2 19-40-70-90-M6
	A.WPF. 115.