


| | | | | |
|--------------------------------------|-----|-------------|----------------|-------|
| 減速比 (Ratio i) | 9 | 12/16/20/32 | 15/40/25/50/30 | 64/80 |
| 額定載重扭矩 (Rated load torque) Nm | 125 | 260 | 230 | 120 |
| 最大加速力矩 (Max. acceleration torque) Nm | 225 | 468 | 414 | 216 |
| 急停扭矩 (Emergency stop torque) Nm | 375 | 780 | 690 | 360 |

| 精密行星减速机技术参数 | | | |
|------------------------------|-----------|--------------------------------|------------------------------|
| 容许最大径向载荷 (Max.radial load) | 1850N | 空载力矩20℃(No-load torque) | ≤ 0.36Nm |
| 容许最大轴向载荷 (Max.axial load) | 2800N | 润滑(Lubrication) | 合成润滑油 (Synthetic grease) |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度 (Operation temperature) | -15℃+90℃ |
| 最大输入转速 (Max input speed) | 6000r/min | 使用寿命 (Service life) | ≥20000h |
| 噪音 (Noise) | ≤ 63db | 防护等级 (Protection grade) | IP54 |
| 回程间隙 (Backlash) | 12arcmin | PL系列 | Tel/电话: 0533-6288333 6288444 |
| | | P2 L2 | Fax/传真: 0533-6288411 |
| | | | Web/网址: www.newstart.cn |

| 未注线性尺寸极限偏差 Unmarked tolerance | |
|----------------------------------|-----------|
| 0.5-3 | ± 0.2 |
| 3-6 | ± 0.3 |
| 6-30 | ± 0.5 |
| 30-120 | ± 0.8 |
| 120-400 | ± 1.2 |
| 400-1000 | ± 2 |

| | |
|--|------|
| <p>精密行星减速机 Precision Planetary Gear Boxes</p> | |
| <p> NEWSTART® 紐氏達特</p> | |
| <p>PF115L2-i-P2-S2 19-40-70-90-M6</p> | |
| A. PF. | 115. |