

1

2

3

4

5



6

A

B

C

D



A

B

C

D

减速比 (Ratio i)		9	12/16/20/32	15/25/40/50/30	64/80
额定承载扭矩 (Rated load torque)	Nm	125	260	230	120
最大加速力矩 (Max. acceleration torque)	Nm	225	468	414	216
急停扭矩 (Emergency stop torque)	Nm	375	780	690	360

精密行星减速机技术参数

容许最大径向载荷 (Max. radial load)	900N	空载力矩20℃ (No-load torque)	$\leq 0.36Nm$
容许最大轴向载荷 (Max. axial load)	1200N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	$\geq 20000h$
噪音 (Noise)	$\leq 68db$	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	16arcmin	PL系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn
		P2 L2	

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

精密行星减速机 Precision Planetary Gear Boxes	
	
WPF115L2-i-P2-S2 35-79-114.3-200-M12	
A. WPF.	115.

1

2

3

4

5

6