



减速比 (Ratio i)	3	4	5	6	8	10	
额定承载扭矩 (Rated load torque) Nm	10	20	18	6	5		
最大加速力矩 (Max. acceleration torque) Nm	18	36	32.4	10.8	9		
急停扭矩 (Emergency stop torque) Nm	30	60	54	18	15		
精密行星减速机技术参数							
容许最大径向载荷 (Max. radial load)	220N	空载力矩20℃ (No-load torque)		≤ 0.05Nm			
容许最大轴向载荷 (Max. axial load)	200N	润滑 (Lubrication)		合成润滑油 (Synthetic grease)			
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃			
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h			
噪音 (Noise)	≤ 58db	防护等级 (Protection grade)		IP54			
回程间隙 (Backlash)	16arcmin	PL系列		Tel/电话: 0533-6288333 6288444			
		P2 L1		Fax/传真: 0533-6288411			
				Web/网址: www.newstart.cn			

未注线性尺寸极限偏差
Unmarked tolerance

0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机
Precision Planetary
Gear Boxes

紐氏達特

PF040L1-i-P2-S2
8-25-30-46-M4

A. PF. 040.