


减速比 (Ratio i)		3	4	5	6	8	10		3-6	±0.3
额定承载扭矩 (Rated load torque) Nm		22	45	41	26	18	15		6-30	±0.5
最大加速力矩 (Max. acceleration torque) Nm		39.6	81	73.8	46.8	32.4	27		30-120	±0.8
急停扭矩 (Emergency stop torque) Nm		66	135	123	78	54	45		120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	480N	空载力矩20℃ (No-load torque)				≤ 0.1Nm			 紐氏達特	PF060L1-i-P2-S2 8-24-38.1-□47.14-M4
容许最大轴向载荷 (Max. axial load)	600N	润滑 (Lubrication)				合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)				-15℃~+90℃				
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h				
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)				IP54				
回程间隙 (Backlash)	10arcmin			PL系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn			A. PF.	060.
				P2 L1						