


减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	6-30	±0.5
额定承载扭矩 (Rated load torque)	Nm	45	41	18	30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	81	73.8	32.4	120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	135	123	54	400-1000	±2
精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	480N	空载力矩20℃ (No-load torque)		≤ 0.1Nm	 PF060L3-i-P2-S2 14-30-50-70-M4	
容许最大轴向载荷 (Max.axial load)	600N	润滑 (Lubrication)		合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)		IP54	A. PF. <span style="color: red;">060.</span>	
回程间隙 (Backlash)	20arcmin	PL系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstar.cn		
		P2 L3				