

1

2

3

4

5

6

A

B

C


D

A

B

C

D

减速比 (Ratio i)		60/64/80/160/256		100/120/200/320		512		6-30		±0.5			
额定承载扭矩 (Rated load torque)		Nm		20		18		5		30-120		±0.8	
最大加速力矩 (Max.acceleration torque)		Nm		36		32.4		9		120-400		±1.2	
急停扭矩 (Emergency stop toque)		Nm		60		54		15		400-1000		±2	
精密行星减速机技术参数									精密行星减速机				
									Precision Planetary Gear Boxes				
容许最大径向载荷 (Max.radial load)		480N		空载力矩20℃ (No-load torque)				≤ 0.1Nm		<div></div> <div>WPF060L3-i-P2-S2 8-25-30-46-M4</div>			
容许最大轴向载荷 (Max.axial load)		600N		润滑 (Lubrication)				合成润滑脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)		3000r/min		使用环境温度 (Operation temperature)				-15℃~+90℃					
最大输入转速 (Max input speed)		6000r/min		使用寿命 (Service life)				≥20000h					
噪音 (Noise)		≤ 63db		防护等级 (Protection grade)				IP54					
回程间隙 (Backlash)		18arcmin				PL系列		Tel/电话: 0533-6288333 6288444					
						P2 L3		Fax/传真: 0533-6288411					
								Web/网址: www.newstart.cn		A.WPF. 060.			

1

2

3

4

5

6