


减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	6-30	±0.5
额定承载扭矩 (Rated load torque) Nm		20	18	5	30-120	±0.8
最大加速力矩 (Max. acceleration torque) Nm		36	32.4	9	120-400	±1.2
急停扭矩 (Emergency stop torque) Nm		60	54	15	400-1000	±2
精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load) 480N		空载力矩20℃ (No-load torque)		≤ 0.1Nm		
容许最大轴向载荷 (Max. axial load) 600N		润滑 (Lubrication)		合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed) 3000r/min		使用环境温度 (operation temperature)		-15℃ ~ +90℃		
最大输入转速 (Max input speed) 6000r/min		使用寿命 (Service life)		≥20000h		
噪音 (Noise) ≤ 63db		防护等级 (Protection grade)		IP54	WPFO60L3-i-P2-S2 14-30-50-70-M5	
回程间隙 (Backlash) 18arcmin		PL系列		A. WPF. 060.		
		P2 L3				
				Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		