

1

2

3

4

5

6

A

B

C

D

A

B

C

D

减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	6-30	±0.5
额定承载扭矩 (Rated load torque) Nm		20	18	5	30-120	±0.8
最大加速力矩 (Max. acceleration torque) Nm		36	32.4	9	120-400	±1.2
急停扭矩 (Emergency stop torque) Nm		60	54	15	400-1000	±2
精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load) 480N					空载力矩20℃ (No-load torque) ≤ 0.1Nm	
容许最大轴向载荷 (Max. axial load) 600N					润滑 (Lubrication) 合成润滑油 (Synthetic grease)	
额定输入转速 (Nominal input speed) 3000r/min					使用环境温度 (Operation temperature) -15℃~+90℃	
最大输入转速 (Max input speed) 6000r/min					使用寿命 (Service life) ≥20000h	
噪音 (Noise) ≤ 63db					防护等级 (Protection grade) IP54	
回程间隙 (Backlash) 18arcmin					PL系列	
					P2 L3	
					Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	
					A. WPF. 060.	