


減速比 (Ratio i)	9	12/16/20/32	15/25/40/50/30	64/80
額定承載扭矩 (Rated load torque) Nm	40	110	90	50
最大加速力矩 (Max. acceleration torque) Nm	72	198	162	90
急停扭矩 (Emergency stop torque) Nm	120	330	270	150

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数				
容许最大径向载荷 (Max.radial load)	900N	空载力矩20℃ (No-load torque)		≤ 0.2Nm
容许最大轴向载荷 (Max.axial load)	1200N	润滑(Lubrication)		合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)		-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h
噪音 (Noise)	≤ 65db	防护等级 (Protection grade)		IP54
回程间隙 (Backlash)	16arcmin	PL系列		Tel/电话: 0533-6288333 6288444
		P2 L2		Fax/传真: 0533-6288411
				Web/网址: www.newstart.cn

	精密行星减速机 Precision Planetary Gear Boxes
	
	WPF080L2-i-P2-S2 14-30-50-70-M4
	A. WPF. 080.